



**University of
Zurich**^{UZH}

**Zurich Open Repository and
Archive**

University of Zurich
Main Library
Strickhofstrasse 39
CH-8057 Zurich
www.zora.uzh.ch

Year: 2015

Deploying an NFC-based inventory system: a case study

Poullie, Patrick ; Bocek, Thomas ; Stiller, Burkhard

Abstract: NFC tags and transceivers are ubiquitous and well supported. Like many academic research groups, the Communication Systems Group CSG of the University of Zürich owns many physical devices, which are required for research and teaching. Traditionally, a printed, human-readable inventory and attached labels have been used to keep track of these devices. A new inventory approach was developed with the aim of simplifying the data acquisition using an NFC tag-based system supported by an Android application. This approach was implemented, tested, and used productively. However, due to technical difficulties - namely, a poor response of NFC tags on metallic material - the NFCbased inventory system did not simplify data acquisition and consequently, the NFC-based inventory system was changed back to the label-based system.

Posted at the Zurich Open Repository and Archive, University of Zurich

ZORA URL: <https://doi.org/10.5167/uzh-116553>

Journal Article

Published Version

Originally published at:

Poullie, Patrick; Bocek, Thomas; Stiller, Burkhard (2015). Deploying an NFC-based inventory system: a case study. *ERCIM News*, (101):41-42.



Special theme:

The Internet of Things and The Web of Things

Also in this issue:

Keynote:

by Cees Links, Founder & CEO
GreenPeak Technologies

Research and Innovation:

Mesh Joinery:
A Method for Building Fabricable
Structures

Deploying an NFC-based Inventory System: A Case Study

by Patrick Poullie, Thomas Bocek and Burkhard Stiller

NFC tags and transceivers are ubiquitous and well supported. Like many academic research groups, the Communication Systems Group CSG of the University of Zürich owns many physical devices, which are required for research and teaching. Traditionally, a printed, human-readable inventory and attached labels have been used to keep track of these devices. A new inventory approach was developed with the aim of simplifying the data acquisition using an NFC tag-based system supported by an Android application. This approach was implemented, tested, and used productively. However, due to technical difficulties - namely, a poor response of NFC tags on metallic material - the NFC-based inventory system did not simplify data acquisition and consequently, the NFC-based inventory system was changed back to the label-based system.

Near Field Communication (NFC) defines a communication channel for devices in close proximity (up to 10 cm) [1]. NFC has a wide range of applications as it can be used to transmit data between devices or between a device and an NFC tag. These tags are standardized – though some differences exist – and the data is stored in the standardized format NDEF (NFC Data Exchange Format) [2]. Depending on the type of tag, data from 48 Bytes (Ultralight) to 888 Bytes (NTAG216) can be stored. The very popular tag NTAG203 and its successor NTAG213 can store 144 Bytes of data. Most Android-based smartphones are equipped with an NFC transceiver, and the software support for NFC has been present since the Android version 2.3, which was released in December 2010. Apple also integrated the NFC technology into iPhone 6 and bases its mobile payment system on this technology, although not providing an open API. Thus, NFC reading and writing capable devices are widespread and ubiquitous.

Inventory System

The label-based Communication Systems Group CSG [3] inventory system for hardware acquisitions above a certain commercial value used a human readable, four character and four digit label. The label had to be printed with a specialized label printer and was attached to the device. The four digit number was used to identify a database entry, which contained information, such as device name, vendor, purchase date, and current holder. Retrieving inventory information about a device involved manually entering its number into a Web browser.

To avoid not only the need for a specialized printer but to also allow every group member to conveniently retrieve and change inventory information, a new tag-based inventory system was envisioned. Barcodes, QR-codes, and RFID tags were evaluated to label items. Bar- and QR-codes were not followed up for two reasons: first, creating human-readable tags would again imply the need for a specialized label printer, which would prohibit “decentralized”



Figure 1: App-based inventory system.

tagging of devices. Second, once these tags are created, information they store is static. This was a major drawback, because the new inventory system has to be able to operate offline, i.e., even without a database connection retrieving or updating inventory information of a device in physical reach had to be possible. Therefore, change of information on a tag and its synchronization later with the database was essential. Consequently, RFID tags had to be used.

Here, NFC tags qualified as the only option, as other RFID tags would require extra hardware for reading and writing tags. This would not only increase costs of the new approach but also reduce user convenience. Thus, since NFC is already supported by many smartphones and tablets, the NFC tags determined a valuable path.

Thus, the human readable inventory labels were replaced with NFC tags, to allow receipt and updating of inventory information upon scanning the tag with an NFC-enabled smartphone. To add a new device a database entry is created via the newly developed inventory smartphone app or via the inventory Web site. An NFC NTAG203 tag is placed on the device and an NFC-capable device used to store this entry's identifier and other essential information in those tags 144 Byte storage. Updating entries is simple: an NFC tag is scanned with the inventory app and all available information about this item is displayed immediately. This information (including location, room, and holder) can be updated within the app, and written to the tag and the database.

The smartphone inventory app was implemented in Java, while the backend was implemented in PHP communicating via HTTPS requests to the smartphone app. Authentication is done with LDAP, while all other data is stored in a MySQL database. Updating of device holders is the most frequently performed action, and the app's starting screen (cf. Figure 1) offers two buttons for this purpose. Upon selecting ‘Lend item’, the name of the new item holder is requested. Once entered, an NFC chip can be scanned, which, like the according data base entry, is updated

accordingly. The 'Return' button deletes the 'current holder' field of the subsequently scanned item (in the data base and on the NFC chip). 'Manipulate item' allows a database entry to be displayed and modified when the corresponding item is scanned. Thus, items can also be added or deleted here. With a 'More' click, additional information and a search function are displayed.

Evaluation

After the NFC-based inventory system was introduced, problems with using this approach in a practical environment soon became apparent. These problems were caused by the poor response of NFC tags, when any metal object was in their vicinity. As even some smartphones have metal cases, this resulted in a poor NFC communication reception. Thus, the evaluation recommends that smartphones with metal case are not used with an NFC-based inventory system. All following evaluations were performed with non-metallic smartphones.

The project identified a smartphone with a good NFC reception, a non-metallic case, and it was also expected to find suitable 'metal-compatible' NFC tags. In particular, explicit metal-shielded tags are expected to work on any surface. The tests utilized metal-

shielded tags ranging in price from a few cents to a few dollars. The cheap metal shielded tags performed as poorly as non-shielded tags, whilst the more expensive ones generally performed better than the low-cost tags. However, the evaluations have shown that even the most expensive and metal-shielded tags failed to work on a large set of metallic items.

Conclusions and Future Steps

Due to these problems with using the NFC system at metal objects, it was decided that an NFC tag-based approach was unacceptably unreliable, and the human-readable label system was reinstated. However, the smartphone app developed is still in use and determines a step forward in the entire inventory process, as it not only allows for an active identification of items – originally planned for by scanning their NFC tag –, but also allows for entering an identifier and all device-related information in a mobile manner, without the need for a Web-based inventory interface.

As very many metallic items were identified as difficult to read, even with current metal-shielded tags, the technology progress of new metal-shielded tags will be tracked in the near future for a possible return to the NFC technology.

Once metal-cased devices work well with a new type of metal-shielded tags, the inventory system will be switched back to an NFC-based inventory system. In conclusion, when planning an introduction of an NFC-based system, it is important to ensure that NFC tags on metallic items can be used by verifying NFC tags operations on metallic items.

References:

- [1] NFC and Contactless Technologies, NFC Forum, URL: <http://nfc-forum.org/what-is-nfc/about-the-technology/>, last access January 2015.
- [2] NFC Data Exchange Format (NDEF) Technical Specification, NFC Forum, URL: http://members.nfc-forum.org/specs/spec_list/, last access January 2015.
- [3] Communication Systems Group CSG, University of Zürich, Switzerland, URL: <http://www.csg.uzh.ch>, last access January 2015.

Please contact:

Patrick Poullie, Thomas Bocek, Burkhard Stiller
Universität Zürich, Switzerland
E-mail: poullie@ifi.uzh.ch,
bocek@ifi.uzh.ch, stiller@ifi.uzh.ch

TrakChain Estimates Costs for Track and Trace in the Internet of (many) Things

by Miguel L. Pardal and José Alves Marques

The TrakChain assessment tools take a description of a physical supply chain – relevant locations, how many goods are received, how often, etc. – and estimate the performance of track and trace queries in a modelled traceability system, providing predictions of how much processing and storage will be required for the working system. The tools were developed at Instituto Superior Técnico, Universidade de Lisboa, Portugal and were evaluated using a Pharmaceuticals supply chain case study.

The Internet of Things (IoT) promises benefits from a deeper connection between the virtual and physical worlds. One specific application area is logistics. The global economy depends on a wide range of supply chains that transfer goods from producers to consumers. The combined use of Enterprise Resources Planning (ERP) and Supply Chain Management (SCM) information systems has greatly improved the overall operational efficiency of supply chains.

However, to achieve further improvements, more up-to-date and precise information about the supply chain is required.

RFID is an IoT technology that allows detailed and automated data capture in the supply chain, as specified by the EPCglobal standards [2]. Tags are attached to the objects of interest and readers placed along the supply chain

locations generate event data, as illustrated in Figure 1.

A practical RFID traceability system should perform adequately for the large number of physical objects flowing in the supply chain [1]; and it should protect the sensitive business data from unauthorized access providing the desired data visibility [2]. The TrakChain project was proposed to evaluate both these aspects. It provides